



SAFETY DATA SHEET

Page : 1

Revised edition no : 1

Date : 18/8/2005

Supersedes : 0/0/0

Gasmixture : O2 (50%) + N2O (50%)**915**Label 2.2 : Non
flammable, non toxic
gas.Label 5.1 : Oxidizing
substances.

O : Oxidizing

1 IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Trade name : Gasmixture : O2 (50%) + N2O (50%)
MSDS No : 915
Company identification : IJSFABRIEK STROMBEEK n.v.
Broekstraat, 70
B-1860 Meise Belgique-Belgie
Tel. +32 2 272 41 34

2 COMPOSITION / INFORMATION ON INGREDIENTS

Substance / Preparation		Preparation.				
Substance name		Contents	CAS No	EC No	Index No	Classification
Oxygen	:		7782-44-7	231-956-9	008-001-00-8	O; R8
Nitrous oxide	:		10024-97-2	233-032-0	-----	O; R8

3 HAZARDS IDENTIFICATION

Hazards identification : Oxidant. Strongly supports combustion. May react violently with combustible materials.
Liquefied gas.

4 FIRST AID MEASURES

- Ingestion : Ingestion is not considered a potential route of exposure.

5 FIRE-FIGHTING MEASURES

Flammable class : Non flammable.
Specific hazards : Supports combustion.
Exposure to fire may cause containers to rupture/explode.
Hazardous combustion products : Nitric oxide/nitrogen dioxide.
Extinguishing media
- Suitable extinguishing media : All known extinguishants can be used.
Specific methods : If possible, stop flow of product.
Move away from the container and cool with water from a protected position.
Special protective equipment for fire fighters : Use self-contained breathing apparatus and chemically protective clothing.

6 ACCIDENTAL RELEASE MEASURES

Personal precautions : Evacuate area.
Ensure adequate air ventilation.
Eliminate ignition sources.
Environmental precautions : Try to stop release.
Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.



SAFETY DATA SHEET

Page : 2

Revised edition no : 1

Date : 18/8/2005

Supersedes : 0/0/0

Gasmixture : O2 (50%) + N2O (50%)**915**

6 ACCIDENTAL RELEASE MEASURES (continued)

Clean up methods : Ventilate area.

7 HANDLING AND STORAGE

Personal protection : Protect eyes, face and skin from liquid splashes.

Storage : Segregate from flammable gases and other flammable materials in store.
Keep container below 50°C in a well ventilated place.

Handling : Open valve slowly to avoid pressure shock.
Suck back of water into the container must be prevented.
Do not allow backfeed into the container.
Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
Refer to supplier's container handling instructions.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection : Do not smoke while handling product.
Ensure adequate ventilation.

Occupational Exposure Limits : Nitrous oxide : TLV© -TWA [ppm] : 50
Nitrous oxide : OEL (UK)-LTEL [ppm] : 100
Nitrous oxide : MAK - Germany [ppm] : 100
Nitrous oxide : HTP-värden - 8 H - [ppm] : 100
Nitrous oxide : HTP-värden - 8 H - [mg/m³] : 180
Nitrous oxide : NGV - [ppm] : 100
Nitrous oxide : NGV - [mg/m³] : 180
Nitrous oxide : KTV - [ppm] : 500
Nitrous oxide : KTV - [mg/m³] : 900

9 PHYSICAL AND CHEMICAL PROPERTIES

Physical state at 20 °C : Liquefied gas.
Liquefied gas.
Liquefied gas.

Colour : Colourless gas.

Odo(u)r : Odourless.

Solubility in water [mg/l] : No reliable data available.

Other data : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

10 STABILITY AND REACTIVITY

Stability and reactivity : May react violently with combustible materials.
May react violently with reducing agents.
Violently oxidises organic material.

12 ECOLOGICAL INFORMATION

Ecological effects information : No known ecological damage caused by this product.

Environmental precautions : Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

Effect on ozone layer : None.



SAFETY DATA SHEET

Page : 3

Revised edition no : 1

Date : 18/8/2005

Supersedes : 0/0/0

Gasmixture : O₂ (50%) + N₂O (50%)**915**

13 DISPOSAL CONSIDERATIONS

- General** : Do not discharge into any place where its accumulation could be dangerous.
Contact supplier if guidance is required.
- Disposal method** : Consult supplier for specific recommendations.

14 TRANSPORT INFORMATION

- UN No.** : 3157
- H.I. nr** : 25
- ADR/RID**
- **Proper shipping name** : LIQUEFIED GAS, OXIDIZING, N.O.S.
 - **ADR Class** : 2
 - **ADR/RID Classification code** : 2 O
 - **Labelling ADR** : Label 2.2 : Non flammable, non toxic gas.
Label 5.1 : Oxidizing substances.
- Other transport information** : Avoid transport on vehicles where the load space is not separated from the driver's compartment.
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
Before transporting product containers :
 - Ensure that containers are firmly secured.
 - Ensure cylinder valve is closed and not leaking.
 - Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
 - Ensure valve protection device (where provided) is correctly fitted.
 - Ensure there is adequate ventilation.
 - Compliance with applicable regulations.

15 REGULATORY INFORMATION

- EC Classification** : O; R8
- EC Labelling**
- **Symbol(s)** : O : Oxidizing
 - **R Phrase(s)** : R8 : Contact with combustible material may cause fire.
 - **S Phrase(s)** : S17 : Keep away from combustible material.

16 OTHER INFORMATION

Receptacle under pressure.
Ensure all national/local regulations are observed.

This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws.

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document